KOMBIC 100 SURFACE



K11SF1523RW930NBB

KOMBIC 100 SF 1500 IP23 9WW RF WFL BK/BK



Description:

Matte black RAL 9011 Finish:

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.218 lm °K: 3000 Plum: 14,1W CRI: 90 Efficacy: 86,3 lm/w R9: 53 UGR: <19 3

MacAdam: Type: СОВ

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power Supply:

220-240V 50/60Hz

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE




K11SF1523RW930NBB


KOMBIC 100 SF 1500 IP23 9WW RF WFL BK/BK


PHOTOMETRIC DATA:


K11SF1523RW930NBB $\eta = 100\%$ Imax = 1293 cd/klm UTE:


CIE: 99 100 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH