KOMBIC 100 SURFACE



K11SF2023RF830NWW

KOMBIC 100 SF 2000 IP23 WW RF FL WH/WH

Description:

Finish: Matte white RAL 9010

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.612 lm °K: 3000 Plum: 14,1W CRI: 80 Efficacy: 114,3 lm/w R9: 80 UGR: <19

MacAdam: 3 Type: СОВ

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

220-240V 50/60Hz

Power Supply:

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE



K11SF2023RF830NWW

KOMBIC 100 SF 2000 IP23 WW RF FL WH/WH


PHOTOMETRIC DATA:


K11SF2023RF830NWW
η = 100%


Imax = 2200 cd/klm

UTE:

CIE: 98 99 100 100 100







KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH