KOMBIC 100 SURFACE



K11SF2023RF840DMB

- KOMBIC 100 SF 2000 IP23 NW RF FL DA M/B

Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.692 lm °K: 4000 Plum: 13,9W CRI: 80 Efficacy: 88,2 lm/w R9: 80 UGR: <19 3 MacAdam:

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE





K11SF2023RF840DMB


KOMBIC 100 SF 2000 IP23 NW RF FL DA M/B

PHOTOMETRIC DATA:

K11SF2023RF840DMB η = 100% Imax = 2200 cd/klm UTE: CIE: 98 99 100 100 100







KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH