# **KOMBIC 100 SURFACE**



K11SF2023RW830DMB

- KOMBIC 100 SF 2000 IP23 WW RF WFL DA M/B

Description:

Finish: metalized polycarbonate mate

Weight: 712 g

Installation: Surface

# **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.538 lm
 % :
 3000

 Plum:
 13,9W
 CRI :
 80

 Efficacy:
 110,6 lm/w
 MacAdam:
 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 13W

Light output tolerance +/- 10%

EPD

# **KOMBIC 100 SURFACE**



K11SF2023RW830DMB


# KOMBIC 100 SF 2000 IP23 WW RF WFL DA M/B


## **PHOTOMETRIC DATA:**


 $K11SF2023RW830DMB $$\eta = 100\%$$$ Imax = 1215 cd/klm$ 

UTE: 1,00A

CIE: 94 97 99 100 100







# **KOMBIC 100 SURFACE**



ACCESORIES:

Suspension



Product code: K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH