KOMBIC 100 SURFACE



K11SF2023RW927DBW

- KOM 100 SF 2000 IP23 9VWW RF WFL DA B/W

Description:

Finish: Matte Traffic white RAL 9016

Weight: 712 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 1.568 lm °K: 2700 Plum: 20W CRI: 90 Efficacy: 78,9 lm/w R9: 58 Type: СОВ 3 MacAdam:

 LED Lifetime:
 50.000 L70 B10 (Ta=25°C)
 Power Supply:
 220-240V 50/60Hz

 Power:
 13W
 Gear:
 Adjustable DALI

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE




K11SF2023RW927DBW


KOM 100 SF 2000 IP23 9VWW RF WFL DA B/W


PHOTOMETRIC DATA:


K11SF2023RW927DBW $\eta = 100\%$ $lmax = 1293 \ cd/klm$ UTE:


CIE: 99 100 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH