KOMBIC 100 SURFACE



K11SF2023RW927NBW

- KOMBIC 100 SF 2000 IP23 9VWW RF WFL B/W

Description:

Finish: Matte black RAL 9011

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.568 lm °K: 2700 Plum: 21,6W CRI: 90 Efficacy: 72,5 lm/w R9: 58 Type: СОВ MacAdam: 3

LED Lifetime: 50.000 L70 B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 13W Gear: Electronic

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE




K11SF2023RW927NBW


KOMBIC 100 SF 2000 IP23 9VWW RF WFL B/W


PHOTOMETRIC DATA:


K11SF2023RW927NBW $\eta = 100\%$ $lmax = 1293 \ cd/klm$ UTE:


CIE: 99 100 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH