KOMBIC 100 SURFACE



K11SF2023RW930DWB

- KOM 100 SF 2000 IP23 9WW RF WFL DA WH/BK

Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 1.784 lm °K: 3000 Plum: 20W CRI: 90 Efficacy: 89,2 lm/w R9: 53 Type: СОВ 3 MacAdam:

 LED Lifetime:
 50.000 L70 B10 (Ta=25°C)
 Power Supply:
 220-240V 50/60Hz

 Power:
 13W
 Gear:
 Adjustable DALI

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE



K11SF2023RW930DWB

KOM 100 SF 2000 IP23 9WW RF WFL DA WH/BK


PHOTOMETRIC DATA:


K11SF2023RW930DWB $_{\eta}$ = 100%


lmax = 1215 cd/klm


UTE: 1,00A


CIE: 94 97 99 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH