KOMBIC 100 SURFACE



K11SF2023RW930NWB

- KOMBIC 100 SF 2000 IP23 9WW RF WFL WH/BK

Description:

Finish: Matte white RAL 9010

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.784 lm °K: 3000 Plum: 21,6W CRI: 90 Efficacy: 82,5 lm/w R9: 53 Type: СОВ MacAdam: 3

LED Lifetime: 50.000 L70 B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 13W Gear: Electronic

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE




K11SF2023RW930NWB


KOMBIC 100 SF 2000 IP23 9WW RF WFL WH/BK


PHOTOMETRIC DATA:


K11SF2023RW930NWB $_{\eta}$ = 100% $_{lmax}$ = 1215 cd/klm UTE: 1,00A


CIE: 94 97 99 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH