KOMBIC 100 SUT

LAMP
Worktitude for light

K11ST2023RF840DBW — **KOMBIC 100 SUT 2000 IP23 NW RF FL DA B/W**

Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.226 lm		**ºK :**	4000
Plum:	13,9W		**CRI :**	80
Efficacy:	114,3 lm/w		**R9 :**	80
UGR:	<19		**MacAdam:**	3
Type:	COB		**Power Supply:**	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)		**Gear:**	Adjustable DALI
Power:	13W			

Light output tolerance +/- 10%

EPD

LAMP
Worktitude for light

K11ST2023RF840DBW　　　　KOMBIC 100 SUT 2000 IP23 NW RF FL DA B/W

PHOTOMETRIC DATA :

K11ST2023RF840DBW

η = 100%

Imax = 2279 cd/klm

UTE:

CIE: 100 100 100 100 100

180°

90°　　　　90°

0°

alpha = 33,1º

100%

BACK　　　FRONT

75%

50,0 %　　　50,0 %

50%

25%

-8H　-4H　0H　4H　8H

04-02-2025

Data according to regulations 2019/2020/EU and 2019/2015/EU