KOMBIC 100 SUT


K11ST2040OP830NRW



KOMBIC 100 SUT 2000 IP40 WW OP BR/WH

Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Shiny metalized interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



BRILLIANT METALLIC POLYCARBONATE Finish:

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.460 lm °K: 3000 Plum: 13,7W CRI: 80 Efficacy: 106,6 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 12W

Light output tolerance +/- 10%



































CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU











KOMBIC 100 SUT



K11ST2040OP830NRW

KOMBIC 100 SUT 2000 IP40 WW OP BR/WH

PHOTOMETRIC DATA:

K11ST2040OP830NRW η = 100% lmax = 974 cd/klmUTE: 1,00A

CIE: 88 100 100 100 100

