


KOMBIC 100 SUT

K11ST2040OP840DMB



KOMBIC 100 SUT 2000 IP40 NW OP DA MA/BK.


Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate

Installation: Suspended
TECHNICAL SPECIFICATIONS:

Light output:	1.474 lm	°K :	4000
Plum:	13,7W	CRI :	80
Efficacy:	107,6 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	12W		

Light output tolerance +/- 10%
**CUSTOM MADE OPTIONS:**

K11ST20400P840DMB **KOMBIC 100 SUT 2000 IP40 NW OP DA MA/BK.**

PHOTOMETRIC DATA :

