KOMBIC 100 SUT



K11ST2523RF840DBW

- KOMBIC 100 SUT 2500 IP23 NW RF FL DA B/W

Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 2.185 lm °K: 4000 Plum: 20W CRI: 80 Efficacy: 102,2 lm/w R9: 80 UGR: <19 3 MacAdam:

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 19W

Light output tolerance +/- 10%

EPD

Tel. +34937366800 Web www.lamp.es

KOMBIC 100 SUT



K11ST2523RF840DBW

KOMBIC 100 SUT 2500 IP23 NW RF FL DA B/W

PHOTOMETRIC DATA:

$$\label{eq:continuous} \begin{split} \text{K11ST2523RF840DBW} \\ \eta &= 100\% \\ \text{Imax} &= 2279 \text{ cd/klm} \\ \text{UTE:} \\ \text{CIE:} \ 100 \ 100 \ 100 \ 100 \ 100 \ 100 \end{split}$$





