### **KOMBIC 100 SUT**


# **TECHNICAL DATA ON REVIEW**

## K11ST2540WF840DWB

# KOMBIC 100 SUT 2500 IP40 NW WFL DA WH/BK

#### Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L70 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low UGR<19. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 1.802 lm °K: 4000 Plum: 21,6W CRI: 80 Efficacy: 83,4 lm/w 3 MacAdam:

UGR: <19 Power Supply: 220-240V 50/60Hz Type: СОВ Gear: Adjustable DALI

LED Lifetime: 50.000 L70 B10 (Ta=25°C)

18W Power:

# Light output tolerance +/- 10%





















### **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU









