


KOMBIC 100 SURFACE TRACK

K11TK1540OP930NWB



KOMBIC 100 TK 1500 IP40 9WW OP WH/BK.

Description:

Downlight to adapt to three-phase track model KOMBIC 100 TK by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010**Weight:** 502 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

Plum:	13,7W	°K :	3000
Type:	COB	CRI :	90
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	R9 :	68
Power:	12W	MacAdam:	3
		Power Supply:	220-240V 50/60Hz
		Gear:	Electronic

**CUSTOM MADE OPTIONS:**