

KOMBIC 100 SURFACE TRACK

K11TK2040OP840DRB



KOMBIC 100 TK 2000 IP40 NW OP DA BR/BK.

Description:

Downlight to adapt to three-phase track model KOMBIC 100 TK by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Shiny metallic interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: BRILLIANT METALLIC POLYCARBONATE**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

Light output:	1.547 lm	°K :	4000
Plum:	13,7W	CRI :	80
Efficacy:	112,9 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	12W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**