

KOMBIC 100 SURFACE TRACK

K11TK2540WF840DBW




KOMBIC 100 TK 2500 IP40 NW WFL DA BK/WH.

Description:

Downlight to adapt to three-phase track model KOMBIC 100 TK by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L70 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011



Installation: 3-Circuit track

TECHNICAL SPECIFICATIONS:

Light output:	1.704 lm	°K :	4000
Plum:	21,6W	CRI :	80
Efficacy:	78,9 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	COB	Gear:	Adjustable DALI
LED Lifetime:	50.000 L70 B10 (Ta=25°C)		
Power:	18W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:

