

## KOMBIC 100 SURFACE TRACK

K11TK2540WF840DMW



## KOMBIC 100 TK 2500 IP40 NW WFL DA MA/WH.

**Description:**

Downlight to adapt to three-phase track model KOMBIC 100 TK by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L70 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** metalized polycarbonate mate**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

|                      |                          |                      |                  |
|----------------------|--------------------------|----------------------|------------------|
| <b>Light output:</b> | 1.792 lm                 | <b>°K :</b>          | 4000             |
| <b>Plum:</b>         | 21,6W                    | <b>CRI :</b>         | 80               |
| <b>Efficacy:</b>     | 83 lm/w                  | <b>MacAdam:</b>      | 3                |
| <b>UGR:</b>          | <19                      | <b>Power Supply:</b> | 220-240V 50/60Hz |
| <b>Type:</b>         | COB                      | <b>Gear:</b>         | Adjustable DALI  |
| <b>LED Lifetime:</b> | 50.000 L70 B10 (Ta=25°C) |                      |                  |
| <b>Power:</b>        | 18W                      |                      |                  |

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**