

KOMBIC 70 DOWNLIGHT



K711523WW840NBB



KOMBIC 70 1500 IP43 NW WW BK/BK

Description:

LAMP Round recessed downlight KOMBIC 70 1500 Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Wallwasher optic option, suitable for vertical plane lighting or work areas surroundings. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 4000K and CRI80. Electronic ON OFF gear included. IP43 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. Available finishes: White and black.

Finish: Matte black RAL 9011**Weight:** 210 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

| | | | |
|----------------------|--------------------------|----------------------|------------------|
| Light output: | 572 lm | °K : | 4000 |
| Plum: | 10W | CRI : | 80 |
| Efficacy: | 57,2 lm/w | MacAdam: | 3 |
| Type: | COB | Power Supply: | 220-240V 50/60Hz |
| LED Lifetime: | 72.000 L80 B10 (Ta=25°C) | Gear: | Electronic |
| Power: | 8,4W | | |

Light output tolerance +/- 10%

K711523WW840NBB

KOMBIC 70 1500 IP43 NW WW BK/BK

PHOTOMETRIC DATA :

