

KOMBIC 70 DOWNLIGHT



K711523WW930NWW



KOMBIC 70 1500 IP43 9WW WW WH/WH

Description:

LAMP Round recessed downlight KOMBIC 70 1500 Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Wallwasher optic option, suitable for vertical plane lighting or work areas surroundings. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 3000K and CRI90. Electronic ON OFF gear included. IP43 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. Available finishes: White and black.

Finish: Matte white RAL 9010**Weight:** 210 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	732 lm	°K :	3000
Plum:	10W	CRI :	90
Efficacy:	73,2 lm/w	R9 :	68
Type:	COB	MacAdam:	3
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	8,4W	Gear:	Electronic

Light output tolerance +/- 10%

KOMBIC 70 DOWNLIGHT

K711523WW930NWW

KOMBIC 70 1500 IP43 9WW WW WH/WH

PHOTOMETRIC DATA :

K711523WW930NWW
 $\eta = 100\%$
 $I_{max} = 1245 \text{ cd/klm}$
 UTE: 1,00B
 CIE: 74 93 99 100 100

