KOMBIC 70 SURFACE



K71SF1540WF927DBB



Description:

LAMP Suspended or ceiling mounting downlight KOMBIC 70 SF 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in black and Wide Flood optic for greater efficiency and to achieve controlled light distribution and low glare level, less than UGR<16. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K and IRC90. Electronic DALI gear included. IP43 rated. Insulation Class I. Photobiological safety group 0. LED life time: 72.000 L80 B10. Available finishes: White and black.



Finish: Matte black RAL 9011

KOMBIC 70 SF 1500 IP43 9VWW WFL D B/B

Weight: 590 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 708 lm °K: 2700 Plum: 10,8W CRI: 90 Efficacy: 65,6 lm/w R9: 61 UGR: 16 MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime:

8,4W Power:

Light output tolerance +/- 10%



CLASE





72.000 L80 B10 (Ta=25°C)

































Gear:

Adjustable DALI

Data according to regulations 2019/2020/EU and 2019/2015/EU

KOMBIC 70 SURFACE





K71SF1540WF927DBB


KOMBIC 70 SF 1500 IP43 9VWW WFL D B/B


PHOTOMETRIC DATA:


K71SF1540WF927DBB η = 100% lmax = 1601 cd/klmUTE:




















KOMBIC 70 SURFACE



ACCESORIES:

Suspension



Product code:

K71SUADLATBK



KOMBIC 70 SF ADAPT. LATERAL CABLE BK



Product code:

K71SUADLATWH

Description:

KOMBIC 70 SF ADAPT. LATERAL CABLE WH



Product code:

K71SUCAWI2000DBK K71SUCAWI2000NBK

Description:

KOMBIC 70 SF ACC. ELEC 5P SUSP 2M BK KOMBIC 70 SF ACC. ELEC 3P SUSP 2M BK



Product code:

K71SUCAWI2000DWH K71SUCAWI2000NWH

Description:

KOMBIC 70 SF ACC. ELEC 5P SUSP 2M WH KOMBIC 70 SF ACC. ELEC 3P SUSP 2M WH