


**K71ST1520RF840DWW**



**KOMBIC 70 SUT 1500 IP20 NW RF FL D W/W**

**Description:**

LAMP Suspended or ceiling mounting downlight KOMBIC 70 SUT 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and Flood reflector for greater efficiency and to achieve controlled light distribution and low glare level, less than UGR<19. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K and IRC80. Electronic DALI gear included. IP20 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. Available finishes: White and black.

**Finish:** Matte white RAL 9010

**Weight:** 650 g

**Installation:** Suspended

**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.232 lm	<b>°K :</b>	4000
<b>Plum:</b>	10,3W	<b>CRI :</b>	80
<b>Efficacy:</b>	119,6 lm/w	<b>MacAdam:</b>	3
<b>UGR:</b>	19	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Type:</b>	COB	<b>Gear:</b>	Adjustable DALI
<b>LED Lifetime:</b>	72.000 L80 B10 (Ta=25°C)		
<b>Power:</b>	8,4W		

*Light output tolerance +/- 10%*



**CUSTOM MADE OPTIONS:**



**PHOTOMETRIC DATA :**

K71ST1520RF840DWW  
 $\eta = 100\%$   
 $I_{max} = 2307 \text{ cd/klm}$   
UTE: 1,00A  
CIE: 92 98 100 100 100

