


KOMBIC 70 SUT

K71ST1520RW840NWW



KOMBIC 70 SUT 1500 IP20 NW RF WFL W/W

Description:

LAMP Suspended or ceiling mounting downlight KOMBIC 70 SUT 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and Wide Flood reflector for greater efficiency and to achieve controlled light distribution and low glare level, less than UGR<19. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K and IRC80. Electronic ON OFF gear included. IP20 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. Available finishes: White and black.

Finish: Matte white RAL 9010

Weight: 610 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.158 lm	°K :	4000
Plum:	10,5W	CRI :	80
Efficacy:	110,3 lm/w	MacAdam:	3
UGR:	19	Power Supply:	220-240V 50/60Hz
Type:	COB	Gear:	Electronic
LED Lifetime:	72.000 L80 B10 (Ta=25°C)		
Power:	8,4W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



PHOTOMETRIC DATA :

K71ST1520RW840NWW
 $\eta = 100\%$
 $I_{max} = 1354 \text{ cd/klm}$
UTE: 1,00A
CIE: 87 96 100 100 100

