


KOMBIC 70 TRACK

K71TK1540OP827NWW



KOMBIC 70 TK 1500 IP40 VWW OP W/W

Description:

LAMP Suspended or ceiling mounting downlight KOMBIC 70 TK 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and opal optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K and IRC80. Electronic ON OFF gear included. IP40 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. White finish.

Finish: Matte white RAL 9010

Weight: 560 g

Installation: 3-Circuit track

TECHNICAL SPECIFICATIONS:

Light output:	892 lm	°K :	2700
Plum:	10,5W	CRI :	80
Efficacy:	84,9 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	8,4W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



PHOTOMETRIC DATA :

K71TK1540OP827NWW
 $\eta = 100\%$
 $I_{max} = 942 \text{ cd/klm}$
UTE: 1,00B
CIE: 75 94 99 100 100

