### LAMPTUB 60 SUSP. CEILING ROSE



### L61SE084LOOC9TWDW

LTUB60 SU RE 840 1200 TW COMF DALI WH



### Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with TW colour temperature with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Matte white RAL 9010 847 x 67 x 80 mm Dimensions:

Installation: Suspended

### **TECHNICAL SPECIFICATIONS:**

Light output: 905 lm °K: TW Plum: 11,7W CRI: 90 Efficacy: 77,4 lm/w 3 MacAdam:

UGR: <19 Power Supply: 220-240V 50/60Hz Type: MID POWER LED Gear: Adjustable DALI DT8

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

8.8W Power:

## Light output tolerance +/- 10%





























## **CUSTOM MADE OPTIONS:**















## LAMPTUB 60 SUSP. CEILING ROSE



L61SE084LOOC9TWDW


## LTUB60 SU RE 840 1200 TW COMF DALI WH


## **PHOTOMETRIC DATA:**


L61SE084LOOC9TWDW  $\eta$  = 100% Imax = 663 cd/klm UTE: 1,00C


CIE: 66 90 99 100 100




















## LAMPTUB 60 SUSP. CEILING ROSE



# ACCESORIES:

## **Assembly**



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.