

LAMP TUB 60 SUSPENDED TRACK

L61ST084MOOC9TWDW

- LTUB60 SUT 840 2400 TW COMF DALI WH

**Description:**

Lamptub 60 model from LAMP to be installed on a suspended rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with TW colour temperature with CRI90. Built-in electronic DALI control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte white RAL 9010**Dimensions:** 847 x 67 x 80 mm**Weight:** 2.140 g**Installation:** Suspended**TECHNICAL SPECIFICATIONS:**

Light output:	1.397 lm	°K :	TW
Plum:	17,9W	CRI :	90
Efficacy:	78 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	MID POWER LED	Gear:	Adjustable DALI DT8
LED Lifetime:	50.000 L80 B10 (Ta=25°C)		
Power:	13.9W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**


LAMPTUB 60 SUSPENDED TRACK



L61ST084MOOC9TWDW

LTUB60 SUT 840 2400 TW COMF DALI WH

PHOTOMETRIC DATA :



ACCESORIES :

Assembly



Product code:
L6SUECB

Description:
LTUB60 ACC. SUR END COVER BK.



Product code:
L6SUECW

Description:
LTUB60 ACC. SUR END COVER WH.



Product code:
L6SUECW3

Description:
LTUB60 ACC. SUR END COVER WE.



Product code:
L6SUECW4

Description:
LTUB60 ACC. SUR END COVER BS.