

MCE1123050PR830NW



- MOD CUSTOM EFF 120X30 5000 WW PR WH

Description:

LAMP MODULAR CUSTOM EFFICIENCY recessed 1200X300 format. Custom option: adaptable to any installation, technical ceiling, finish or technical aspects by the needs of the project. Made of steel, prismatic diffuser of translucent polycarbonate and an optical film to control light distribution and reduce glare UGR <19. Model for MID-POWER LED, 3000K colour temperature and IRC 80. Control gear included. With a protection rating of IP23. Insulation class II. Photobiological safety group 0. Lifetime: 50.000 L80 B10.

Finish: Matte Traffic white RAL 9016


Dimensions: 1.200 x 300 x 59,3 mm

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	3.666 lm	°K :	3000
Plum:	31W	CRI :	80
Efficacy:	118,3 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	MID POWER	Gear:	Electronic
LED Lifetime:	50.000 L80 B10 (Ta=25°C)		
Power:	28W		

Light output tolerance +/- 10%

**CUSTOM MADE OPTIONS:**

MCE1123050PR830NW MOD CUSTOM EFF 120X30 5000 WW PR WH

PHOTOMETRIC DATA :

