Product datasheet

MINI SHOT LED

Worktitude for light

MN230SP840NA



SHOT 120 G2 2900 NW SP ANT.

Description:

Outdoor spotlight model SHOT 120 2900, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Textured anthracite

Weight: 3.212 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 2.215 lm
 °K:
 4000

 Plum:
 23W
 CRI:
 80

 Efficacy:
 96,3 lm/w
 MacAdam:
 3

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 20W

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:






























MINI SHOT LED




MN230SP840NA

SHOT 120 G2 2900 NW SP ANT.

PHOTOMETRIC DATA:





alpha = 11,4°	H (m)	D (m)	Emax	Emed
\bigwedge	1	0,20	32881	21894
	2	0,40	8220	5473
	3	0,60	3653	2433
	4	0,80	2055	1368

Product datasheet

MINI SHOT LED



ACCESORIES:

Optical



Product code:

Description:

MSSC134B SHOT 120 ACC. ANTIGLARE SCREEN.