


### QROD12624MF830D



# QUIET RECTANGLE OCULT 2x6 2400 WW MFL D

### Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET RECTANGLE OCULT 2x6 .Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, dø. LOW VOC and Low formaldehyde emissions. Luminaire model OD1RE612MF830DBB 3000K and CRI80. Electronic DALI gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.



Installation: Suspended

### **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.160 lm
 °K:
 3000

 Plum:
 28W
 CRI:
 80

 Efficacy:
 77,1 lm/w
 MacAdam:
 3

 UGR:
 <10</td>
 Power Supply:
 100-240V 50/60Hz

 Type:
 HIGH POWER LED
 Gear:
 Adjustable DALI

**LED Lifetime:** 50.000 L90 B10 (Ta=25°C)

Power: 12W

## Light output tolerance +/- 10%















## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU



















### QROD12624MF830D


## QUIET RECTANGLE OCULT 2x6 2400 WW MFL D

## **PHOTOMETRIC DATA:**

OD1RE612MF830NBB  $\eta$  = 100% Imax = 4606 cd/klm UTE: CIE: 102 100 100 100 100







Data according to regulations 2019/2020/EU and 2019/2015/EU





