Worktitude for light


QROD12936WF830N



QUIET RECTANGLE OCULT 2x9 3600 WW WFL

Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET RECTANGLE OCULT 2x9 .Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, dø. LOW VOC and Low formaldehyde emissions. Luminaire model OD1RE918WF830NBB 3000K and CRI80. Electronic ON OFF gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.



Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 3.240 lm
 °K:
 3000

 Plum:
 40W
 CRI:
 80

 Efficacy:
 82,4 lm/w
 MacAdam:
 3

UGR: <16

Type: HIGH POWER LED

LED Lifetime: 50.000 L90 B10 (Ta=25°C)

Power: 18W

Light output tolerance +/- 10%















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU











Power Supply:

Gear:





120-277V 50/60Hz

Electronic



QUIET RECTANGLE OCULT 2x9 3600 WW WFL

PHOTOMETRIC DATA:

OD1RE918WF830NBB η = 100% lmax = 1615 cd/klm UTE: CIE: 99 100 100 100 100

