


QR0D12936WF840D

QUIET RECTANGLE OCULT 2x9 3600 NW WFL D
Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET RECTANGLE OCULT 2x9. Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, d0. LOW VOC and Low formaldehyde emissions. Luminaire model OD1RE918WF840DBB 4000K and CRI80. Electronic DALI gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	3.240 lm	°K :	4000
Plum:	40W	CRI :	80
Efficacy:	82,4 lm/w	MacAdam:	3
UGR:	<16	Power Supply:	220-240V 50/60Hz
Type:	HIGH POWER LED	Gear:	Adjustable DALI
LED Lifetime:	50.000 L90 B10 (Ta=25°C)		
Power:	18W		


Light output tolerance +/- 10%


CUSTOM MADE OPTIONS:


QROD12936WF840D

QUIET RECTANGLE OCULT 2x9 3600 NW WFL D

PHOTOMETRIC DATA :



Essential Colours



Trendy Colours



Prime Colours

